



Toll free: 877-453-4778  
 Phone: 405-324-1777  
 Fax: 405-324-1778  
[sales@firstsling.com](mailto:sales@firstsling.com)

## FULL INSPECTION ROUND SLING TECHNOLOGY®






### The Inspectable Roundslings®

U.S. Patent #747926, Canadian Patent #2,614,374,  
 Australian Patent #2006259277  
 Other U.S., Canadian, and Foreign Patents Pending

### FP POLYESTER ROUND SLINGS

#### FIRST® POLYESTER ROUND SLINGS

#### DESIGN FACTOR 7:1 RATED CAPACITY IN KILOGRAMS

Code No	 Vertical	 Choker	 90° Basket	 60° Basket	 45° Basket	Approximate Measurements			
						Body Diameter mm	Connection Hardware Min. Dia. mm	Width at Load mm	Sling Weight Per Meter kgs
FP 7M10	1,000	800	2,000	1,700	1,400	19.05	12.70	15.75	0.37
FP 7M20	2,000	1,600	4,000	3,400	2,800	22.86	15.75	22.35	0.52
FP 7M30	3,000	2,400	6,000	5,100	4,200	25.40	19.05	25.40	0.74
FP7M40	4,000	3,200	8,000	6,800	5,600	31.75	22.35	31.75	0.97
FP 7M50	5,000	4,000	10,000	8,500	7,000	40.64	28.45	41.15	1.19
FP 7M60	6,000	4,800	12,000	10,200	8,400	41.91	31.75	44.45	1.65
FP 7M80	8,000	6,400	16,000	13,600	11,200	44.45	35.05	47.75	1.79
FP 7M100	10,000	8,000	20,000	17,000	14,000	54.61	38.10	50.80	2.38
FP 7M120	12,000	9,600	24,000	20,400	16,800	62.23	41.15	60.45	2.68
FP 7M150	15,000	12,000	30,000	25,500	21,000	76.20	47.75	69.85	3.57
FP 7M200	20,000	16,000	40,000	34,000	28,000	82.55	53.85	76.20	4.46
FP 7M300	30,000	24,000	60,000	51,000	42,000	95.25	63.50	88.90	5.73

#### Warning

Do not exceed a sling's rated lifting capacity.

All users must be trained in sling selection and inspection and rigging practices.

For more information visit us at [www.firstsling.com](http://www.firstsling.com)