



Toll free: 877-453-4778
 Phone: 405-324-1777
 Fax: 405-324-1778
sales@firstsling.com

FULL INSPECTION ROUND SLING TECHNOLOGY®

The Inspectable Roundslings®

U.S. Patent #7,475,926, Canadian Patent #2,614,374,
 Australian Patent #2006259277
 Other U.S., Canadian, and Foreign Patents Pending

FP POLYESTER ROUND SLINGS

FIRST® POLYESTER ROUND SLINGS

DESIGN FACTOR 5:1 RATED CAPACITY IN POUNDS

Code No	Vertical	Choker	90° Basket	60° Basket	45° Basket	Approximate Measurements			
						Body Diameter Inches	Connection Hardware Min. Dia. Inches	Width at Load Inches	Sling Weight Per Foot lbs
FP 30	3,000	2,400	6,000	5,100	4,200	0.75	0.50	0.62	0.25
FP 40	4,000	3,200	8,000	6,800	5,600	0.80	0.50	0.62	0.30
FP 60	6,000	4,800	12,000	10,200	8,400	0.90	0.62	0.88	0.35
FP 90	9,000	7,200	18,000	15,300	12,600	1.00	0.75	1.00	0.50
FP 120	12,000	9,600	24,000	20,400	16,800	1.25	0.88	1.25	0.65
FP 140	14,000	11,200	28,000	23,800	19,600	1.30	1.00	1.38	0.70
FP 170	17,000	13,600	34,000	28,900	23,800	1.60	1.12	1.62	0.80
FP 230	23,000	18,400	46,000	39,100	32,200	1.65	1.25	1.75	1.11
FP 260	26,000	20,800	52,000	44,200	36,400	1.75	1.38	1.88	1.20
FP 320	32,000	25,600	64,000	54,400	44,800	2.15	1.50	2.00	1.60
FP 400	40,000	32,000	80,000	68,000	56,000	2.45	1.62	2.38	1.80
FP 540	54,000	43,200	108,000	91,800	75,600	3.00	1.88	2.75	2.40
FP 680	68,000	54,400	136,000	115,600	95,200	3.25	2.12	3.00	3.00
FP 900	90,000	72,000	180,000	153,000	126,000	3.75	2.50	3.50	3.85

Warning

Do not exceed a sling's rated lifting capacity.

All users must be trained in sling selection and inspection and rigging practices.

For more information visit us at www.firstsling.com